

RECHARGEABLE

INTRANT™ DUAL-LIGHT ANGLE LIGHT



HEAD ROTATES 90°

45°

EXCLUSIVE
DOWNWARD FLOODLIGHT


GRAB-N-GO
CHARGING BASE



Head rotates 90° - directing beam exactly where it's needed most



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches independently control separate LEDs



Heavy-duty, clip and V-ring securely holds tight to gear in any situation



ALSO AVAILABLE IN SAFETY RED.

205 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

DUAL-LIGHT ANGLE LIGHT

RECHARGEABLE

ITEM NUMBER/UPC

XPR-5568RX (Red), 0 17398 80631 2
 XPR-5568RXLB (Red, Light & Battery Only), 0 17398 80697 8
 XPR-5568GX (Green), 0 17398 80630 5

CERTIFICATIONS

- CE, cULus, ATEX, IECEx, InMetro, UKCA, KOSHA
 - Meets requirements of NFPA

PATENTS

- 9,713,217 10,119,663

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 200L, 7 hrs. runtime
 - MEDIUM: 110L, 15 hrs. runtime
 - LOW: 60L, 27 hrs. runtime
 - STROBE

FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime
 - MEDIUM: 40L, 15 hrs. runtime
 - SURVIVAL: 20L, 27 hrs. runtime

DUAL-LIGHT

- 205L, 7 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 40,256
 - MEDIUM: 15,625
 - LOW: 8,750

BEAM DISTANCE

FLASHLIGHT

- HIGH: 401m
 - MEDIUM: 250m
 - LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
 - WIDTH: 2.6 in (66mm)
 - DEPTH: 2.6 in (66mm)
 - HEAD DIAMETER: 2.1 in (53mm)
 - WEIGHT: 10.6 oz (301g)(with batteries)

BATTERY







- Rechargeable Li-ion battery pack
 - AA Battery carrier (batteries not included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Angle light
 - Rechargeable Li-ion battery pack
 - AA battery carrier
 - Snap-in rapid charger (Charge Input: 24VDC max) Meets requirements of NFPA
 - AC & DC power supplies
 - Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	7h	27h	7h
	401m		
	40256cd		
			
			

UL LISTED
 E 457735
 ID 400354

Bayco Product, Inc. XPR-5568
 640 S. Sanden Blvd., Wylie, TX 75098

For use with Bayco Lion Battery Pack 5568-BATT or 5568-CARRIER with 3 AA Energizer Type EN91 or E91 batteries only
 Para uso con a batería de iones de litio Bayco 5568-BATT or 5568-CARRIER con 3 baterías AA Energizer Tipo EN91 or E91

CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV1 GRPS E-G T130°C CLASS I ZONE 0 AEx ia IIC T4 Ga

© 1987 Ex ia op in IMA Ex ia op in IMA Ex ia op in IIC T4 Ga

ELECTRICAL SAFETY INTRINSICALLY SAFE SECURITE INTRINSEQUE

US Patents 9,713,217 & 10,119,663

CE 2575 **UK CA** 0359

Meets the requirements of NFPA-1971-8.6 (2013)

DEMKO 17 ATEX 1927 UL2008C009 IECEx UL 17.0082 22-AV480-0250X 3.3VDC Alkaline 3.7VDC Li-ion IP-67 Um: 10V

Control Drawing: 5568-CERT-DWG-1-03
 For Battery Charger Connection see Instruction Manual Drawing: 5562-68-MECH-DWG-1-09

SEE INSTRUCTION MANUAL VORR MANUEL MFG MM-YY

